

CYLINDER-HEAD CASTING NUMBERS & SPECIFICATIONS (BASIC CASTING 6090)					
ENGINE	YEAR	CASTING NUMBER	COMBUSTION-CHAMBER VOLUME (CC)	VALVE DIAMETER (INCHES) INTAKE/EXHAUST	COMMENTS
221	62-63	C2OE-A, B, C, D, E C3OE-A	45	1.59/1.39	
255	80	E0SE-AC	55.4	1.67/1.45	
260	62-63	C2OE-F C3OE-B	54.5	1.59/1.39	
	64	C4OE-B	54.5	1.67/1.45	
289	63-64	C3AE-F C3OE-E, F C4AE-C C5DE-B C6DE-G *C6OE-C, E C6OE-M *C7OE-A *C7OE-B C7OE-C *C7OZ-B *C7ZE-A *C8OE-D, L, M	54.5 54.5	1.67/1.45 1.67/1.45	*May be machined to accept air-pump plumbing. Rail-type rocker arms.
	68		63	1.67/1.45	
HP289	63	C3OE	49.2	1.67/1.45	Screw-in studs and integral valve-spring cups.
	64-67	C4OE-B C5OE-A C5AE-E	54.5	1.78/1.45	
302	68-70	C8OE-F C7OE-C, G C8AE-J C8DE-F C8OE-J, M *C8OE-K, L C9TE-C D0OE-B D1TZ-A D2OE-BA	53.5 63 58.2	1.78/1.45	Used with 4-V engine.
	71-74	D5OE-GA, -A3A, -A3B	58.2	1.78/1.45	Internal air-injection ports.
	75-76	D7OE-DA	69	1.78/1.45	
	77	D8OE-AB	69	1.78/1.45	S/A 351W, stamped rocker arms.
	78-80				
Boss 302	69	C9ZE-A	63	2.23/1.71	
	70	D0ZE-A D1ZE-A	58	2.19/1.71	
351W	69-74	C9OE-B, D D0OE-C, G D0OZ-C D5TE-EB D8OE-AB	60.4 60.4 69	1.84/1.54 1.84/1.54 1.78/1.45	Internal air-injection ports. S/A 302, stamped rocker arms.